

**Description**

AW ISO 32 5000 HOUR

<b>Inspection Information</b>	<b>Test Method</b>	<b>Typical Value</b>
Gravity, °API	ASTM D287	32.44
Specific Gravity at 60°F (15.6°C)	ASTM D4052	0.8631
Flash Point, °C	ASTM D92	210
Flash Point, °F	ASTM D92	410
Viscosity at 40°C, cSt	ASTM D445	32.11
Viscosity at 100°C, cSt	ASTM D445	5.55
Viscosity Index	ASTM D2270	110
Pour Point, °C (°F)	ASTM D5950	-39°C (-38°F)
Oxidation Hours	ASTM D943	5,000
Color	ASTM D1500	0.5
Zinc, wt. %	ASTM D5185	0.043
Phosphorus, wt. %	ASTM D5185	0.034
Sulfur, wt. %	ASTM D4951	0.071



## Claims Information

ASTM D6158	Recommended For
Bosch Rexroth	Recommended For
Cincinnati/MAG IAS P-68	Recommended For
DIN 51524-2	Recommended For
Eaton E-FDGN-TB002-E, 35VQ25A	Recommended For
General Motors LS-2	Recommended For
ISO 6743	Recommended For
ISO 11158	Recommended For
JCMAS HK	Recommended For
Parker Denison HF-0, HF-1	Recommended For
Parker Denison HF-2	Recommended For
Racine	Recommended For
US Steel 127, 136	Recommended For
Vickers/Eaton M-2950-S, I-286-S	Recommended For
ISO 11158	Recommended For

