



HD Conventional Green 50/50

Heavy Duty Coolant

DESCRIPTION

HD Green 50/50 is a conventional ethylene glycol-based coolant and anti-freeze solution designed for heavy-duty engines. This pre-mixed low silicate formula provides excellent protection against freezing, boiling, and corrosion, ensuring optimal engine performance and longevity in extreme conditions.

APPLICATIONS

Heavy Duty 50/50 Coolant is suitable for a wide range of heavy-duty applications: including:

- Trucks
- Buses
- Construction equipment
- Agricultural machinery
- Industrial generators

BENEFITS

- Exceptional heat transfer and cooling performance to maintain engine temperature within optimal ranges.
- Contains advanced corrosion inhibitors to safeguard engine components and extend their lifespan.
- Protects against freezing at low temperatures and prevents boiling at high temperatures, preventing engine damage.
- Designed to work with a wide range of heavy-duty diesel engines.
- The 50/50 pre-mixed formula eliminates the need for dilution, saving time and reducing the risk of incorrect dilution ratios.
- Provides long-lasting protection, reducing maintenance frequency. Note: this product is not an extended life coolant.



HD Conventional Green 50/50

Heavy Duty Coolant

TYPICAL PROPERTIES

TEST PARAMETER	METHOD	TYPICAL
Water concentration (wt%)	ASTM D1123	47%
Specific Gravity @ 15 °C	ASTM D4052	1.077
Freezing Point, °F	ASTM D3321	-40
pH	ASTM D1287	10.3
Color	Visual	Green

Average values only. Minor variations are to be expected during normal manufacturing.
Avoid prolonged exposure to sunlight; UV light may diminish color.

MEETS:

- ASTM D3306
- ASTM D4985
- ASTM D6210
- TMC RP 329
- Cummins CES14603
- Navistar
- Caterpillar
- Freightliner 48-22880
- Volvo GM
- John Deere 8650-5
- SAE 1941
- Case Corp. MS1710
- MACK
- Ford New Holland 9-86
- EMD M.I. 1748E
- GM 1899
- GM 1825
- Detroit Diesel 7SE298
- PACCAR
- Thermo-King
- Waukesha 4-1974D
- CID A-A 52624A